

Hanger Lightweight Boom Headset

An ultra-light and simple headset that integrates into almost any style of head gear and suits multiple applications from construction to law enforcement.

FEATURES

- Simple yet effective design can be worn with almost any style of head gear
- Easy to install and remove
- Comfortable to wear

TECHNICAL DATA

Weight:	47g
Mic sensitivity:	-46 +/- 4 dB
Mic directivity:	Noise cancelling
Speaker impedance:	16 Ohm
Operating temperature:	-20 to +60°C (continuous)
Operating voltage:	1.3 to 10 VDC
Cable:	Straight, 6 conductor shielded



Industries



Rugged Breeze Headset with Wireless PTT

An adjustable behind the head headset with an adjustable noise cancelling microphone. Fitted with a round 45mm body PTT. Headset supplied with a wireless PTT and handlebar mounting bracket. User applications include from police cycle teams and crane operators to control room applications.

FEATURES

- Adjustable behind-the-head style band with single left earphone
- Suitable for use under a helmet or cap
- Fitted with in-line round 55mm PTT
- Supplied with wireless PTT suitable for mounting on handlebars/gearsticks

TECHNICAL DATA

Weight:	130g
Connector:	Radio specific
Microphone:	Electret boom
PTT:	In-line body & wireless
Colour:	Black only



Industries



Sidewinder Behind The Neck Headset

A rugged behind the neck headset catering for communication needs in highly active environments.

FEATURES

- Rugged headset
- Robust and highly flexible boom
- Incorporates a noise cancelling microphone element
- Bendable steel headband is over moulded with thermo plastic rubber for comfort and durability

TECHNICAL DATA

Weight:	80g
Mic sensitivity:	-43 +/- 3 dB
Speaker impedance:	88 Ohm
Colour:	Matt Black



Industries



MP-H Multi Purpose Headset



A multi purpose headset for professionals using helmets. It mounts into most helmet types and can be used in high-noise areas, at high speed or in heavy wind.

FEATURES

- Flexible boom microphone
- All-round mounting system
- Quick-release connector
- Fits all types of headgear
- Adapts to SAVOX Com-Control units
- Replaceable hygienic windshield

TECHNICAL DATA

Weight:	25g
Microphone output:	2,2 kOhm @ 1 kHz, noise-canceling, adjustable boom
Cable:	ø 4mm, 270mm, coiled
Speaker bag for integral helmets:	Included
Holder for headband mounting:	Included
Operating temperature:	-25 to +63°C (continuous)
Connector:	4-pole quick-release connector
Speaker impedance:	32 Ohm

OPTIONS (on selected models)

- Headband
- Version with twin speakers



Standards / Features



Industries

